


PROJECT	DATE
TYPE	QTY

IP68 FLEXIBLE LED STRIPS WITH SILICONE INJECTED TUBE



IL-TG-3535-RGB
Thinglow Reel

SPECIFICATIONS

Dimensions: 500*12*0.25mm
LED Qty: 60 LED per meter (18 ft.)
LED Type: RGB
Lumens Per Foot: 300
Voltage: DC24
Power Consumption: 10.2W/FT
Waterproof Grade: IP68 Waterproof

DESCRIPTION:

The Thinglow 3535 Series is a Flexible Printed LED Circuit Board that provides high quality even illumination and variable brightness. Bends for easy installation with variable cutting units for each model number. Available in different colors. 12 or 24VDC. Suitable for both indoor & outdoor decorative applications.

FEATURES:

1. SMD 3535 LED as lighting sources
2. Different colors available
3. Input voltage: 24V
4. Every 6-LED are cuttable for 24V strips
5. White, Black, Yellow PCB Board are available

APPLICATION

- Decorative lighting for festivals, events, shows, exhibitions
- Architectural lighting for canopy, corridor, window, archway
- Backlight or edge light for signage
- Path or contour marking
- Channel letter lighting



MODEL NUMBER	COLOR	LED QTY.	(NM) / (CT:K)	LUMINOUS FLUX	WORK VOLTAGE	POWER	VIEW ANGLE	PACKING
IL-TG-3535-RGB-24	RGB	SMD 3535 120/m	R: 620-630 G: 510-525 B: 455-470	R: 55-60 G: 125-135 B: 50-55	DC24V	10.2W/FT	120°	5m(16.4')/reel

IMPACT LIGHTING INC.