

PROJECT	DATE
TYPE	QTY

## SUPER HIGH ULTRA BRIGHT THINGLOW



**IL-TG-RGBX**  
5M Thinglow Reel

### DESCRIPTION:

- Input voltage: DC 12V, DC24V
- Super bright top SMD 5050 LED as lighting sources
- Different colors are available
- Every 3-LED are cuttable for 12V strips, 6 LEDs are cuttable for DC24V
- White, Black, Yellow PCB Board are available
- 3M adhesive tape included on backside

### APPLICATION

- Decorative lighting for festivals, events, shows, exhibitions
- Architectural lighting for canopy, corridor, window, archway,
- Backlight or edge light for signage
- Path or contour marking
- Channel letter lighting

### SPECIFICATIONS

Dimensions: 500\*12\*0.22mm









LED Qty: 60 LED per meter

Voltage: DC12V, DC24

Power Consumption: 19.2W/m

Waterproof Grade: IP20-IP67

Four Chips in One LED

Model No.	Color	LED Qty	$\lambda$ (Nm)/(CT:K)	Luminous Flux	PCB Dimensions (mm)	Work Voltage	Power	Water proof	Packing				
IL-F5050A30-CP4-12/24	 RGB Pure White	60/m	■: 620-630 ■: 465-470 ■: 520-525 ■: 590-595	■: 100-120 ■: 90-110 ■: 250-270 ■: 100-120	500*12*0.22	DC12V DC24V	19.2W/m	No	5m/reel				
IL-F5050A30-CN4-12/24	 RGB Nature White												
IL-F5050A30-CW4-12/24	 RGB Warm White												
IL-F5050A30-CY4-12/24	 RGB Amber												
IL-F5050C30-CP4-12/24	 RGB Pure White	60/m	□: 6000-6500K □: 4000-4500K □: 3000-3500K	□: 350-390 □: 340-360 □: 300-330				500*12*0.22		DC12V DC24V	19.2W/m	IP67	5m/reel
IL-F5050C30-CN4-12/24	 RGB Nature White												
IL-F5050C30-CW4-12/24	 RGB Warm White												
IL-F5050C30-CY4-12/24	 RGB Amber												

### IMPACT LIGHTING INC.

2101 West Central Blvd. Orlando, Florida 32805 USA • Phone: 1.800.507.5714 • Email: sales@impactlightinginc.com

[www.impactlightinginc.com](http://www.impactlightinginc.com)