

PROJECT	DATE
TYPE	QTY

**IP 68 UNDERWATER LED STAINLESS STEEL FIXTURE**



**UX 50**

**DESCRIPTION:**

The **UX-50** Stainless Steel LED Underwater Fixture features a rugged 316 stainless steel housing with a 10mm thick tempered glass lens over a powerful 10W CREE high lumen output, high efficacy LED, available in warm white, neutral white, cool white and RGB+W configurations.


With an IP68 rating the UX-50 is designed and engineered for outdoor and underwater use. This compact fixture is a powerhouse with a range of 45 to 90+ lumens per Watt.

**FEATURES:**


- No Visible LED Spots
- IP68
- 316 Stainless Steel
- 10mm tempered glass lens
- 10W CREE LED
- 4 LED color option

**SPECIFICATIONS**

Material	316 Stainless Steel
Cover	Tempered Glass (T=10mm)
IP Rating	IP68
Typical Power Consumption	10W
Input Voltage	350mA/700mA
Control	DMX512 / ON/ OFF
DMX Channel	4CHS (RGBW) @ DMX512 Control
Light Source	CREE
LED Chip Range	XP-E/XM-L High Lumen Output, High Efficacy
LED Quantity	1PCS
Color/CCT	3000K / 4000K / 6500K / RGBW
CRI	Ra ≥ 80
Lifespan	50,000 hrs.
Beam Angle	25°
Product Size	Ø2" x 1.5" x 1.9" Ø50mm 39mm 49mm
Weight	0.9LBS / 0.41KG
Environment Parameter	Work Temperature -25°~45°
Storage Humidity	0~90°



**SWIVEL U BRACKET**



**PHOTOMETRICS**

LED	TYPICAL LIGHT EFFICIENCY
3000K	>55LM/W
4000K	>65LM/W
6000K	>90LM/W
RGB	>45LM/W

**ORDERING**

MODEL	LED	LED TYPE	ACCESSORIES
UX-50 12VDC - 10W LED Underwater Fixture	WW - 3000K NW - 4000K CW - 6500K RGB+W - Red/Green /Blue/White	CC - Constant Current CV - Constant Voltage DMX - 5 Wire for RGB+W	RF - RF Controller + Handheld Remote SB - Swivel U Bracket DMX4 - 4 Channel DMX512 Decoder for RGB+W DE3 - STICK-DE3 DMX Wall Controller RS232 - Advanced RS232 Serial Controller EPICWIFI - WiFi for Advanced RS232 Serial Cont.

**IMPACT LIGHTING**