

PROJECT	DATE
TYPE	QTY.



ARCHITECTURAL LINEAR SERIES







mounting clip





frosted cover black opal cover

XTRU-5552 (raw aluminum shown black finish available)

The XTRU-5552 mounting channel utilizes LED tape light and is easily placed on horizontal or vertical surfaces allowing you to create your own custom LED low voltage lighting scheme.

XTRU-5552 LED Profile is a small durable fixture designed for unique applications with designers and

This versatile IP67* profile is suitable for custom recessed

installation in walls and ceilings. This high quality profile offers an unique way to make use of linear low voltage lighting and is the designer's choice for commercial and

FEATURES


- IP65 rating after install
- concealable flange


architects in mind.

- easy install mounting clips

residential LED strip lighting.

- black and anodized aluminum available
- frosted and black opal cover options
- endcaps included










NO CONNECTOR

Endcap w/ Hole **Endcap Closed**

ENDCAPS



Example: **ORDERING**

XTRU-5552- 48"- NA - F - CW - R - 48 - C

XTRU-5552 Profile, 48" Cut Length, Non-Anodized Aluminum Finish, Frosted Cover w/ Cool White LED, Right Facing Lead Wire, 12" Wire Length, Closed End Cap

MODEL	CUT LENGTH	HOUSING FINISH	COVER	LED COLOR	LEAD WIRE LOCATION	LEAD WIRE LENGTH	END CAP
XTRU-5552		_	-	-			-
Aluminum	Write desired	NA - Non-Anodized	F - Frosted	WW - Warm White	R - Right Facing	Write Desired	C - Closed
LED Lighted	length above	BA- Black Anodized	BO - Black Opal	CW - Cool White	L - Left Facing	Length Above	H - Hole
Profile				NW - Neutral White	B - Left & Right*		
				RGB - Red Green Blue	(daisy chain)		

Impact Lighting Inc.

^{*}IP67 relies on proper sealing on install.



PROJECT	DATE
TYPE	QTY.

XTRU-5552

ARCHITECTURAL LINEAR SERIES

