



OPTI-PURE™  
Sideglow® application



*Suitable for interior and exterior applications, Opti-Pure™ Sideglow® cable is UV protected and has an exterior jacket that is algacide and fungicide treated for maximum durability against the elements. Sideglow® cable is strong enough for amusement park rides, extreme cold weather as well as underwater applications. With no heat or electricity in the cable, typical lighting design restrictions are eliminated, creating a multitude of design possibilities.*


The only manufacturer of  
Fiber Optic Cable In The U.S.A.



- ▶ Heat Free Illumination
- ▶ Underwater Safe
- ▶ Flexible
- ▶ Energy Efficient
- ▶ Safe Neon Alternative
- ▶ Durable
- ▶ Color Changing Capability
- ▶ Low Maintenance




PROJECT	DATE
TYPE	QTY




**OPTI-PURE™** 23 strand side emitting perimeter cable, .25" (6.35mm) x .61 (15.5mm)  
1" Minimum Bend Radius = .1" (25.4mm) **200ft Maximum Run**

MODEL #	LENGTH	CTN. WEIGHT
OP23SG-125	125 ft.	11 lbs.
OP23SG-150	150 ft.	13 lbs.
OP23SG-200	200 ft.	19 lbs.
OP23SG-500	500 ft.	48 lbs.
OP23SG-1000	1000 ft.	1000 lbs.




**OPTI-PURE™** 32 strand side emitting perimeter cable, .5/16" diameter" (7.9mm)  
1" Minimum Bend Radius = .1" (25.4mm) **200ft Maximum Run**

MODEL #	LENGTH	CTN. WEIGHT
OP32SG-125	125 ft.	8 lbs.
OP32SG-150	150 ft.	9 lbs.
OP32SG-200	200 ft.	12 lbs.
OP32SG-500	500 ft.	35 lbs.
OP32SG-1000	1000 ft.	58 lbs.



**OPTI-PURE™** 42 strand side emitting perimeter cable, .3/8" diameter" (9.5mm)  
1" Minimum Bend Radius = .1/2" (25.4mm) **200ft Maximum Run**

MODEL #	LENGTH	CTN. WEIGHT
OP42SG-125	125 ft.	6 lbs.
OP42SG-150	150 ft.	7 lbs.
OP42SG-200	200 ft.	9 lbs.
OP42SG-500	500 ft.	31 lbs.
OP42SG-1000	1000 ft.	50 lbs.



**OPTI-PURE™** 84 strand side emitting perimeter cable, .5" diameter" (12.7mm)  
1" Minimum Bend Radius **200ft Maximum Run**

MODEL #	LENGTH	CTN. WEIGHT
OP84SG-125	125 ft.	6 lbs.
OP84SG-150	150 ft.	7 lbs.
OP84SG-200	200 ft.	9 lbs.
OP84SG-500	500 ft.	31 lbs.
OP84SG-1000	1000 ft.	50 lbs.



**OPTI-PURE™** 126 strand side emitting perimeter cable, .625" diameter" (15.9mm)  
1/2" Minimum Bend Radius **200ft Maximum Run**

MODEL #	LENGTH	CTN. WEIGHT
OP126SG-125	125 ft.	6 lbs.
OP126SG-150	150 ft.	7 lbs.
OP126SG-200	200 ft.	9 lbs.
OP126SG-500	500 ft.	31 lbs.
OP126SG-1000	1000 ft.	50 lbs.

